

USER MANUAL

Bloody Mary



CONGRATULATIONS ON YOUR PURCHASE OF BLOODY MARY, THE ULTIMATE DISTORTION PEDAL FOR SHRED-DERS.

Bloody Mary delivers a truly wicked distortion that's never generic. An alchemist's blend of precision controls makes sure that your sound is yours alone - a lethal potion of razor gain, tone and body. You'll find an overview of the controls on the next page.

BLOODY MARY controls

- GAIN** controls the degree of distortion. Experiment to get the edge you want - but don't max it out if you're afraid of hurting yourself!
- LEVEL** sets the overall volume, no matter what the gain. Use it with a "level" head - this pedal is loud.
- LOW** takes you to a subterranean universe of power for thumping chords and sublime leads that reach as deep as they soar high.
- MID** controls the sweet spot that gives you fullness and body. Pull it back for a classic metal sound. Crank it up to go grunge.
- HIGH** unleashes a blitzkrieg of searing sonic pleasure. Turn it all the way up, and it will cut through solid steel. Handle with care.
- BODY** delivers a rich extra fill by boosting lower-mids and lows. Kick it in to give your sound an extra lift at critical moments.



Size Box	100x120x35mm + Switches/ knobs on top 6mm + Knobs on bottom 3mm.
Connections	INPUT-Jack 6,3mm. OUTPUT-Jack 6,3mm. DC-Jack 2mm pin. Center pin negative.
Power supply	9 volt DC or battery 9V Alkaline.
Power consumption	30 milli Amperes.
Weight	500 gram packed in a box.
Battery	Open the battery-cover on the back using a flat-tipped screwdriver in the slot.

Technical specs

Input Impedance @ 1KHz	937KOhm
Output Impedance@1KHz	1,2KOhm
Power supply	9V DC (Power tool 9)
Minimum Power supply Voltage	8V DC
Maximum Power supply Voltage	12,5V DC
Current Draw @ 9V DC	30mA
Maximum input signal Vp/p	2,5Vp/p
Battery Type	9V battery 6F22
Battery Life	3 to 5 Hour
External connectors	Input Jack, Output Jack, 9V DC Jack
Controls	On/Off, Level, Comp, Gain, Low, Mid, High, Body
Depth	120mm
Width	100mm
Height	55mm
Weight (excl. battery)	0,495Kg

T-REX WARRANTY CONDITIONS

T-Rex offers a 2-year warranty on all our products. In the unlikely event of a malfunction, please contact our technical support at info@t-rex-engineering.com before sending us the product for repair. When the product has been sent to us at sender's cost, we will repair or replace your product and send it back to you - free of charge and usually within 3 weeks (shipping not included). The product needs to be accompanied by a copy of your receipt, serial number, return address, phone number, e-mail address and a brief explanation of the problem. Please note that we cannot replace a product until we have received it here in Denmark.

The warranty is lost if the product has been damaged by alteration, misuse, accident, or neglect; or if the product has been repaired or serviced by persons not authorized by T-Rex. Read more about warranty conditions at www.t-rex-engineering.com.

ABOUT T-REX

Based in Vejle, Denmark, T-Rex Engineering makes classic and signature effects pedals for the world's best musicians. Our approach blends hi-tech innovation with old-world craftsmanship – always in the service of killer tone.

EU REGULATIONS • ENVIRONMENT PROTECTION

T-Rex accepts and follows the regulations and directives issued by the EU. Actually we find these environment protecting regulations very good, and we are happy to follow them.



ISSUED IN VEJLE, 2009



Steen Meldgaard Laursen
Managing Director



Lars Dahl-Jørgensen
Development Director



Sebastian Jensen
Production Director



T-Rex Engineering ApS, Tel.: +45 75 72 71 81, Fax: +45 75 72 71 98
www.t-rex-engineering.com • mail: info@t-rex-engineering.com